EXAMPLE OF LIMITATION OF 2/3 SMF

- 1. The following example will demonstrate that if ß is large compared to φ (the ratio tan \$\mathbb{S}/\tan $\varphi > 0.56$), the value of the horizontal earth pressure coefficient computed from Coulomb's equation using an SMF of 2/3 will exceed the value of the horizontal pressure coefficient computed from the Danish Code equation. In some cases, this increase will be overly conservative.
- 2. For a smooth (no wall friction), vertical wall with a soil having ϕ = 30° and ß = 21°, the horizontal earth pressure coefficients will be computed by the Danish Code equation and Coulomb's equation.

Danish Code Equation (Equation 3-5, EM 1110-2-2502)

$$K_o = (1 - \sin \phi)(1 + \sin \beta)$$

= $(1 - \sin 30^\circ)(1 + \sin 21^\circ)$
= 0.6792

Coulomb's Equation with SMF = 2/3 (Equation 3-14, EM 1110-2-2502)

$$\phi_d = \tan^{-1} (SMF \tan \phi)$$

$$= \tan^{-1} (2/3 \tan 30^\circ)$$

$$= 21.0517^\circ$$

$$K_{o} = \frac{\cos^{2} \phi_{d}}{\left[1 + \sqrt{\frac{\sin \phi_{d} \sin (\phi_{d} - \beta)}{\cos \delta \cos \beta}}\right]^{2}}$$

$$= \frac{\cos^{2} 21.057^{\circ}}{\left[1 + \sqrt{\frac{\sin 21.0517^{\circ} \sin (21.0517^{\circ} - 21^{\circ})}{\cos 21^{\circ}}}\right]^{2}}$$

$$= 0.8394$$

ETL 1110-2-322 15 Oct 90

Coulomb's Equation with SMF = 0.7319 (from Table in Enclosure 5 for ϕ = 30°)

$$\phi_{d} = \tan^{-1} (SMF \tan \phi)$$

$$= \tan^{-1} (0.7319 \tan 30^{\circ})$$

= 22.9071

$$K_o = \frac{\cos^2 22.9071^{\circ}}{\left[1 + \sqrt{\frac{\sin 21.0517^{\circ} \sin (22.9071^{\circ} - 21^{\circ})}{\cos 21^{\circ}}}\right]^2}$$

= 0.6791

3. From the summary of the results below, Coulomb's equation with an SMF of 2/3 results in an at-rest earth pressure coefficient which exceeds the Danish Code equation.

At-rest, Danish Code equation: $K_o = 0.6792$

Coulomb's equation with SMF = 2/3: $K_o = 0.8394$

Coulomb's equation with SMF = 0.7319: $K_o = 0.6791$